安仁國際股份有限公司
ANNREN TECHNOLOGIES CO., LTD.

Tel : +886-6-313-0155
Fax : +886-6-313-0225
E-mail : sales@annren.com
No.196-19, Zhonghua Rd., Yongkang Dist., Tainan City 71069, Taiwan

4POS High Voltage Plastic Shell Connector With Shield（REL2）

Describe

- 4POS
- Plastic shell
- With secondary locking, delayed unlocking
- Anti-mis-touch design(IPXXB)
- High Protection Degree：
- 4 Anti-mistake key positions
- Cable Section：2.5mm²--6mm²
- Integrated Mask Interlocking Function
- For battery heating, compressor, PTC、OBC、PDU equipment

Applicantion

- Current rating：16A=2.5mm
  25A=4mm
  40A=6mm
- voltage rating ：1000V DC
- Shield：Option
- HVIL：Option
- temperature range：-40℃--+140℃

Ordering information

REL2-T 4 P A H -2.5 -B

- Design Extension Number
- Cable：2.5/4/6
- H:HVIL
- Key position：A、B、C、D
- P：Shield
- POS:4
- T:Plug；Z：Socket
- Serial No.

Note: Plug does not contain power terminals, socket does not contain power and interlocking terminals

Size

PLUG



Flange Socekt



Socket install hole size



Key	L	Note
A	8 mm	
B	10.6mm	

Note: panel roughness is not less than 0.4, flatness is not less than 0.2.